

## PMI 531

264531



PMIopen - Operator panel with 12.1" touchscreen, open HMI platform for every common visualisations software, configurable with PMI Assistant.

## Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian)
Resolution:	800 x 600
Display type:	TFT
Display diagonal:	12.1 Zoll
Colour depth:	65536
Touchscreen:	Resistive
Possible PMI applications:	PSS/PSSu/PNOZmulti;PNOZmulti diagnostics;Diagnostics PSS / SafetyBUSp
Number of Ethernet interfaces:	1
Number of RS 232 interfaces:	1
Supply voltage (V):	24,0
Supply voltage type:	DC
Operating system:	Windows Embedded CE 6.0
Width dimension:	352.0 mm
Height dimension:	276.0 mm
Depth dimension:	63.3 mm
Gross weight:	5005 g
Net weight:	2860 g
Ambient temperature:	0 - 50 °C

## Optional accessories




261905

RT-Licence PVIS OPC-Srv f.PMI, PtoP



261906

RT-Licence PVIS OPC-Srv f.PMI, 8 devices



269700

power connector PMI (3 pcs)



269701

seal for PMIvisu, PMlopen, PMImicro



310300

Serial programming cable



313100

SD Memory Card 512MB

265010

Zenon Operator Dev 1024

265210

Zenon Operator RT PMI

265220

Zenon Operator 7.20 RT PMI



THE SPIRIT OF SAFETY

265020

Zenon Operator 7.20 Dev 1024

---