

## PSSu E F PS

312190



Electronic module to supply power (periphery, 24 V, system 5 V, passive).

## Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;KOSHA
Application range:	Standard/failsafe
Power consumption DC:	9.0 W
Supply voltage (V):	24,0
Supply voltage type:	DC
Purpose of supply voltage:	Module Supply
Permitted base modules:	PSSu BS 1/8C;PSSu BS 1/8S;PSSu BS-R 1/8C;PSSu BS-R 1/8S
Width dimension:	12.6 mm
Height dimension:	76.0 mm
Depth dimension:	60.2 mm
Gross weight:	47 g
Net weight:	39 g
Ambient temperature:	0 - 60 °C

## Accessories



312650

PSSu BS 1/8 S



312651

PSSu BS 1/8 C



312652

PSSu BS-R 1/8 S



312653

PSSu BS-R 1/8 C

## Optional accessories



312900

PSSu A ET (10 pcs.)



312901

PSSu A ETM (2 pcs.)



312902

PSSu A EC



312949

PSSu A ET PE (10 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)