

PSSu E F PS1

312191



Electronic module to supply power (periphery 24 V, system 5 V, buffered).

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;KOSHA
Application range:	Standard/failsafe
Power consumption DC:	12.0 W
Supply voltage (V):	24,0
Supply voltage type:	DC
Purpose of supply voltage:	Module Supply
Permitted base modules:	PSSu BS 2/8C;PSSu BS 2/8S;PSSu BS-R 2/8C;PSSu BS-R 2/8S
Width dimension:	25.2 mm
Height dimension:	76.0 mm
Depth dimension:	60.2 mm
Gross weight:	66 g
Net weight:	57 g
Ambient temperature:	0 - 60 °C

Accessories



312654

PSSu BS-R 2/8 S



312655

PSSu BS-R 2/8 C



312656

PSSu BS 2/8 S



312657

PSSu BS 2/8 C

Optional accessories



312900

PSSu A ET (10 pcs.)



312901

PSSu A ETM (2 pcs.)



312902

PSSu A EC



312949

PSSu A ET PE (10 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)