

PSSu E F DI OZ 2

312220



Electronic module digital inputs and outputs, with failsafe function, 1 input, 1 output, 2-pole 2 A.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;KOSHA
Application range:	Failsafe
Number of digital inputs:	1
Number of 2-pole semiconductor outputs:	1
Number of test pulse outputs:	1
Protection type, housing:	IP20
Permitted base modules:	PSSu BP 1/12C;PSSu BP 1/12S;PSSu BP 1/8C;PSSu BP 1/8S;PSSu BP-C 1/8C;PSSu BP-C 1/8S;PSSu BP-C1 1/12C;PSSu BP-C1 1/12S
Width dimension:	12.6 mm
Height dimension:	76.0 mm
Depth dimension:	60.2 mm
Gross weight:	44 g
Net weight:	35 g
Ambient temperature:	0 - 60 °C

Accessories



312600

PSSu BP 1/8 S



312601

PSSu BP 1/8 C



312610

PSSu BP-C 1/8 S



312611

PSSu BP-C 1/8 C



312618

PSSu BP 1/12 S



312619

PSSu BP 1/12 C



312622

PSSu BP-C1 1/12 S



312623

PSSu BP-C1 1/12 C

Optional accessories



312900

PSSu A ET (10 pcs.)



312901

PSSu A ETM (2 pcs.)



312902

PSSu A EC



312949

PSSu A ET PE (10 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)
