

## PSSu E S 4AI U

312445



Electronic module analogue inputs and outputs, with standard function, 4 inputs, 0 ... 10 V (se).

## Technical details

Certifications:	CE;cULus Listed
Application range:	Standard
Number of analogue inputs:	4
Protection type, housing:	IP20
Permitted base modules:	PSSu BP 1/12C;PSSu BP 1/12S;PSSu BP 1/8C;PSSu BP 1/8S;PSSu BP-C 1/12C;PSSu BP-C 1/12S;PSSu BP-C 1/8C;PSSu BP-C 1/8S
Width dimension:	12.6 mm
Height dimension:	76.0 mm
Depth dimension:	60.2 mm
Gross weight:	45 g
Net weight:	37 g
Ambient temperature:	0 - 60 °C

## Accessories



312600

PSSu BP 1/8 S



312601

PSSu BP 1/8 C



312610

PSSu BP-C 1/8 S



312611

PSSu BP-C 1/8 C



312618

PSSu BP 1/12 S



312619

PSSu BP 1/12 C



312620

PSSu BP-C 1/12 S



312621

PSSu BP-C 1/12 C

## Optional accessories



312900

PSSu A ET (10 pcs.)



312901

PSSu A ETM (2 pcs.)



312902

PSSu A EC



312949

PSSu A ET PE (10 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)