

## PSSu E S 2DOR 2

312511



Electronic module , standard function, 2 relay outputs potential-free (2 A).

### Technical details

Certifications:	CE;cULus Listed
Application range:	Standard
Number of relay outputs:	2
Protection type, housing:	IP20
Permitted base modules:	PSSu BP 1/12C;PSSu BP 1/12S;PSSu BP 1/8C;PSSu BP 1/8S;PSSu BP-C 1/8C;PSSu BP-C 1/8S;PSSu BP-C1 1/12C;PSSu BP-C1 1/12S
Width dimension:	12.6 mm
Height dimension:	76.0 mm
Depth dimension:	60.2 mm
Gross weight:	50 g
Net weight:	42 g
Ambient temperature:	0 - 60 °C

### Accessories



312600

PSSu BP 1/8 S



312601

PSSu BP 1/8 C



312610

PSSu BP-C 1/8 S



312611

PSSu BP-C 1/8 C



312618

PSSu BP 1/12 S



312619

PSSu BP 1/12 C



312622

PSSu BP-C1 1/12 S



312623

PSSu BP-C1 1/12 C

## Optional accessories



312900

PSSu A ET (10 pcs.)



312901

PSSu A ETM (2 pcs.)



312902

PSSu A EC



312949

PSSu A ET PE (10 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)