

## PSSu H PLC1 FS SN SD-T

314070



Head module, SafetyNET p RTFN, SD card PL e, SIL CL 3.

### Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV
Application in accordance with:	IEC 61508;ISO 13849-1
Product standard:	EN 61131-2
Permitted number of expansion modules:	64
Power consumption DC:	16.0 W
Protection type, housing:	IP20
Width dimension:	130.0 mm
Height dimension:	125.6 mm
Depth dimension:	83.7 mm
Gross weight:	413 g
Net weight:	378 g
Ambient temperature:	-40 - 70 °C

### Accessories



313110

PSSu A Con 1/4 S (2 pcs.)












313111

PSSu A Con 2/8 C (2 pcs.)

## Optional accessories

	312065	PSSu H m F DP SN SD
	312085	PSSu H FS SN SD
	312900	PSSu A ET (10 pcs.)
	312901	PSSu A ETM (2 pcs.)
	312949	PSSu A ET PE (10 pcs.)
	312958	PSSu A LA0 (10 x 108 pcs.)
	312967	PSSu A LA0.1 (10 x 108 pcs.)
	313100	SD Memory Card 512MB
	314902	PSSu A EC-T

	380000	SafetyNET p Cable per mtr
	380001	SN CAB RJ45s RJ45s, 0,5m
	380003	SN CAB RJ45s RJ45s, 1m
	380005	SN CAB RJ45s RJ45s, 2m
	380007	SN CAB RJ45s RJ45s, 5m
	380009	SN CAB RJ45s RJ45s, 10m
	380400	SafetyNET p Connector RJ45s
	380600	PSSnet SLL 5T
	380602	PSSnet SHL 6T 2FMMS MRP



380650

PSSnet SHL 6T 2FSMSC MRP

---



380604

PSSnet SLL 4T 1FMMS

---



312071

PSSu H PLC1 FS DP SN SD

---



314085

PSSu H FS SN SD-T

---



312066

PSSu H m F DPsafe SN SD

---



314071

PSSu H PLC1 FS SN SD M12-T

---