

## PSSu E S 2AI I se-T

314450



Electronic module analogue inputs and outputs, with standard function, 2 inputs 0 ... 20 mA, 4 ... 20 mA, ext. temperature.

### Technical details

Certifications:	CE;cULus Listed;TÜV
Application range:	Standard
Number of analogue inputs:	2
Protection type, housing:	IP20
Permitted base modules:	PSSu BP 1/8C-T;PSSu BP 1/8S-T;PSSu BP-C 1/8C-T;PSSu BP-C 1/8S-T
Width dimension:	12.6 mm
Height dimension:	76.0 mm
Depth dimension:	60.2 mm
Gross weight:	44 g
Net weight:	36 g
Ambient temperature:	-40 - 70 °C

### Accessories



314600

PSSu BP 1/8 S-T



314601

PSSu BP 1/8 C-T



314610

PSSu BP-C 1/8 S-T



314611

PSSu BP-C 1/8 C-T

## Optional accessories



312900

PSSu A ET (10 pcs.)



312901

PSSu A ETM (2 pcs.)



312949

PSSu A ET PE (10 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)



314902

PSSu A EC-T