


## PSSu E S INC 24V se -T

314486



Electronic module analogue inputs and outputs, with standard function, 1 incremental encoder 24 V, 1-pole, ext. temperature.

### Technical details

|                           |   |
|---------------------------|---|
| Certifications:           | CE;TÜV  |
| Application range:        | Standard  |
| Protection type, housing: | IP20  |
| Permitted base modules:   | PSSu BP 2/16C;PSSu BP 2/16S;PSSu BP-C 2/16C;PSSu BP-C 2/16S |
| Width dimension:          | 25.2 mm   |
| Height dimension:         | 76.0 mm   |
| Depth dimension:          | 60.2 mm   |
| Gross weight:             | 57 g  |
| Net weight:               | 48 g  |
| Ambient temperature:      | -40 - 70 °C   |

### Accessories



314628

PSSu BP 2/16 S-T




314629

PSSu BP 2/16 C-T



314630

PSSu BP-C 2/8 S-T



314631

PSSu BP-C 2/8 C-T

## Optional accessories



312900

PSSu A ET (10 pcs.)



312901

PSSu A ETM (2 pcs.)



312949

PSSu A ET PE (10 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)



314902

PSSu A EC-T