

PSSu H PLC1 FS SN SD-R

315070



Head module, SafetyNET p RTFN, SD card, Railway PL e, SIL CL 3.

Technical details

Certifications:	CE;TÜV
Application in accordance with:	EN 50125-3;EN 50126;EN 50128;EN 50129;EN 50155;IEC 61508;ISO 13849-1
Product standard:	EN 50126;EN 50128;EN 50129;EN 50155;EN 61131-2
Permitted number of expansion modules:	64
Power consumption DC:	16.0 W
Protection type, housing:	IP20
Width dimension:	130.0 mm
Height dimension:	125.6 mm
Depth dimension:	83.7 mm
Gross weight:	415 g
Net weight:	350 g
Ambient temperature:	-40 - 70 °C

Accessories



313110










PSSu A Con 1/4 S (2 pcs.)



313111

PSSu A Con 2/8 C (2 pcs.)

Optional accessories

	312900	PSSu A ET (10 pcs.)
	312901	PSSu A ETM (2 pcs.)
	312949	PSSu A ET PE (10 pcs.)
	312958	PSSu A LA0 (10 x 108 pcs.)
	312967	PSSu A LA0.1 (10 x 108 pcs.)
	313100	SD Memory Card 512MB
	314902	PSSu A EC-T
	380000	SafetyNET p Cable per mtr
	380001	SN CAB RJ45s RJ45s, 0,5m



380003

SN CAB RJ45s RJ45s, 1m



380005

SN CAB RJ45s RJ45s, 2m



380007

SN CAB RJ45s RJ45s, 5m



380009

SN CAB RJ45s RJ45s, 10m



380400

SafetyNET p Connector RJ45s



380600

PSSnet SLL 5T



380602

PSSnet SHL 6T 2FMMSC MRP



380650

PSSnet SHL 6T 2FSMSC MRP



380604

PSSnet SLL 4T 1FMMSC



315085

PSSu H FS SN SD-R