

PIT es Set3s-5c 400437





PITestop E-STOP/contact block set consisting of illuminated E-STOP pushbutton with E-STOP symbol and logo, and contact block with monitoring. 2 N/C, with spring-loaded terminals.

Cetrifications: CE Product standard: EN 60947-5-5;EN ISO 13850 Release type: Rotational Actuator: Pushbutton Printing symbol: Pilz logo and E-STOP symbol Colour button: Red Protective collar: No Self-monitored: Yes Terminal type: Spring-loaded terminal Number of N/C: 2 Supply voltage (V): 12,0 - 30,0 Supply voltage type: AC/DC Protection type, housing: IP65 Mounting type: Front panel installation Diameter of mounting cut-out: 22.3 mm Width dimension: 56.0 mm Height dimension: 92.0 mm Gross weight: 88 g Net weight: 75 g	Technical details	
Release type: Rotational Actuator: Pushbutton Printing symbol: Pilz logo and E-STOP symbol Colour button: Red Protective collar: No Self-monitored: Yes Terminal type: Spring-loaded terminal Number of N/C: 2 Supply voltage (V): 12,0 - 30,0 Supply voltage type: AC/DC Protection type, housing: IP65 Mounting type: Front panel installation Diameter of mounting cut-out: 22.3 mm Width dimension: 92.0 mm Gross weight: 88 g	Certifications:	CE
Actuator: Printing symbol: Printing symbol: Printing symbol: Protective collar: Protective collar: No Self-monitored: Yes Terminal type: Spring-loaded terminal Number of N/C: 2 Supply voltage (V): 12,0 - 30,0 Supply voltage type: AC/DC Protection type, housing: IP65 Mounting type: Front panel installation Diameter of mounting cut-out: 22.3 mm Width dimension: 92.0 mm Gross weight: 88 g	Product standard:	EN 60947-5-5;EN ISO 13850
Printing symbol: Colour button: Red Protective collar: No Self-monitored: Terminal type: Spring-loaded terminal Number of N/C: 2 Supply voltage (V): 12,0 - 30,0 Supply voltage type: AC/DC Protection type, housing: IP65 Mounting type: Front panel installation Diameter of mounting cut-out: 22.3 mm Width dimension: 56.0 mm Height dimension: 92.0 mm Gross weight:	Release type:	Rotational
Colour button: Protective collar: No Self-monitored: Yes Terminal type: Spring-loaded terminal Number of N/C: 2 Supply voltage (V): 12,0 - 30,0 Supply voltage type: AC/DC Protection type, housing: IP65 Mounting type: Front panel installation Diameter of mounting cut-out: 22.3 mm Width dimension: 56.0 mm Height dimension: 92.0 mm Gross weight:	Actuator:	Pushbutton
Protective collar: Self-monitored: Yes Terminal type: Spring-loaded terminal Number of N/C: 2 Supply voltage (V): 12,0 - 30,0 Supply voltage type: AC/DC Protection type, housing: IP65 Mounting type: Front panel installation Diameter of mounting cut-out: 22.3 mm Width dimension: 56.0 mm Height dimension: 92.0 mm Gross weight: 88 g	Printing symbol:	Pilz logo and E-STOP symbol
Self-monitored: Terminal type: Spring-loaded terminal Number of N/C: 2 Supply voltage (V): 12,0 - 30,0 Supply voltage type: AC/DC Protection type, housing: IP65 Mounting type: Front panel installation Diameter of mounting cut-out: 22.3 mm Width dimension: 56.0 mm Height dimension: 92.0 mm Gross weight: 88 g	Colour button:	Red
Terminal type: Spring-loaded terminal Number of N/C: 2 Supply voltage (V): Supply voltage type: AC/DC Protection type, housing: IP65 Mounting type: Front panel installation Diameter of mounting cut-out: 22.3 mm Width dimension: 56.0 mm Height dimension: 92.0 mm Gross weight: 88 g	Protective collar:	No
Number of N/C:2Supply voltage (V):12,0 - 30,0Supply voltage type:AC/DCProtection type, housing:IP65Mounting type:Front panel installationDiameter of mounting cut-out:22.3 mmWidth dimension:56.0 mmHeight dimension:92.0 mmGross weight:88 g	Self-monitored:	Yes
Supply voltage (V): Supply voltage type: AC/DC Protection type, housing: Mounting type: Front panel installation Diameter of mounting cut-out: 22.3 mm Width dimension: 56.0 mm Height dimension: 92.0 mm Gross weight:	Terminal type:	Spring-loaded terminal
Supply voltage type: Protection type, housing: Mounting type: Front panel installation Diameter of mounting cut-out: 22.3 mm Width dimension: 56.0 mm Height dimension: 92.0 mm Gross weight: 88 g	Number of N/C:	2
Protection type, housing: Mounting type: Front panel installation Diameter of mounting cut-out: 22.3 mm Width dimension: 56.0 mm Height dimension: 92.0 mm Gross weight:	Supply voltage (V):	12,0 - 30,0
Mounting type: Diameter of mounting cut-out: Width dimension: Height dimension: Gross weight: Front panel installation 22.3 mm 56.0 mm 92.0 mm	Supply voltage type:	AC/DC
Diameter of mounting cut-out: Width dimension: Height dimension: Gross weight: 22.3 mm 56.0 mm 92.0 mm	Protection type, housing:	IP65
Width dimension: 56.0 mm Height dimension: 92.0 mm Gross weight: 88 g	Mounting type:	Front panel installation
Height dimension: 92.0 mm Gross weight: 88 g	Diameter of mounting cut-out:	22.3 mm
Gross weight: 88 g	Width dimension:	56.0 mm
	Height dimension:	92.0 mm
Net weight: 75 g	Gross weight:	88 g
	Net weight:	75 g
Ambient temperature: -25 - 55 °C	Ambient temperature:	-25 - 55 °C