

PSEN 2.1b-20/PSEN 2.1-20 /8mm/10m/1unit

502227



Magnetic safety switch 1NO/1NC, square design. IP6K9K, operating distance 8 mm, height design 13 mm PU = 1 piece with actuator, with 10 m cable (PUR).

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;ECOLAB
Sensor principle:	magnetic
Number of N/O:	1
Number of N/C:	1
Max. current of safe contacts:	0.01 A
Connection type:	10m Kabel
Switching voltage:	24 V
Type of switching voltage:	DC
Assured switching distance:	8.0 mm
Assured release distance:	26.0 mm
Protection type, housing:	IP67;IP69
Status indicator:	Without LED
Design:	square
Width dimension:	26.0 mm
Height dimension:	36.0 mm
Depth dimension:	13.0 mm
Gross weight:	357 g
Net weight:	340 g
Ambient temperature:	-25 - 70 °C
Operating modes:	Series connection

Optional accessories



380308

PSS67 M12 connector, straight, male, 5pole



380310

PSS67 M12 connector, angled, male, 5pole



532110

PSEN Winkel / bracket



534310

PSEN Distanzplatte / spacer (10 pcs.)



534320

PSEN reverse spacer



535110

PSEN i1 Interface for 4 PSEN 2



540310

PSEN screw M4x16 10pcs