

PSEN 2.1b-26/PSEN2.1-20/8mm/10m/EX/1unit

502250



Magnetic safety switch 1NO/1NC, square design, IP6K9K, operating distance 8 mm, height design 13 mm PU = 1 piece with actuator, with 10 m cable (PUR), ATEX approval.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);ATEX;TÜV;ECOLAB;electrosuisse
Sensor principle:	magnetic
Number of N/O:	1
Number of N/C:	1
Max. current of safe contacts:	0.01 A
Connection type:	10m Kabel
Switching voltage:	24 V
Type of switching voltage:	DC
Assured switching distance:	8.0 mm
Assured release distance:	26.0 mm
Protection type, housing:	IP67;IP69
Status indicator:	Without LED
Design:	square
Width dimension:	26.0 mm
Height dimension:	36.0 mm
Depth dimension:	13.0 mm
Gross weight:	360 g
Net weight:	340 g
Ambient temperature:	-25 - 55 °C
Operating modes:	Series connection

Optional accessories



380308

PSS67 M12 connector, straight, male, 5pole



380310

PSS67 M12 connector, angled, male, 5pole



532110

PSEN Winkel / bracket



534310

PSEN Distanzplatte / spacer (10 pcs.)



534320

PSEN reverse spacer



535110

PSEN i1 Interface for 4 PSEN 2



540310

PSEN screw M4x16 10pcs