

PSEN 1.1a-22/PSEN 1.1-20 /8mm/5m/ix1/1un

504228



Magnetic safety switch 2 N/O, square design. Height design 13 mm IP6K9K, operating distance 8 mm, for applications with PSEN ix1 PU = 1 piece with actuator, with 5 m cable (PUR).

## Technical details

Housing material:	PBT
Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;ECOLAB
Sensor principle:	magnetic
Number of N/O:	2
Connection type:	5m Kabel
Switching voltage:	24 V
Type of switching voltage:	DC
Assured switching distance:	8.0 mm
Assured release distance:	26.0 mm
Protection type, housing:	IP67;IP69
Status indicator:	Without LED
Design:	square
Width dimension:	26.0 mm
Height dimension:	36.0 mm
Depth dimension:	13.0 mm
Gross weight:	210 g
Net weight:	192 g
Ambient temperature:	-10 - 70 °C
Operating modes:	Series connection

## Accessories



535120

PSEN ix1 Interface for 4 PSEN 1

## Optional accessories



532110

PSEN Winkel / bracket



534310

PSEN Distanzplatte / spacer (10 pcs.)




534320

PSEN reverse spacer



535120

PSEN ix1 Interface for 4 PSEN 1



540310

PSEN screw M4x16 10pcs