

PSEN 1.2p-22/PSEN 1.2-20/8mm/ix1/ 1unit

505222



Magnetic safety switch 2 N/O, 4-pin M8 male connector, round M30 design IP67, operating distance 8 mm, for applications with PSEN ix1 PU = 1 piece with actuator.

Technical details

Housing material:	PBT
Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV
Sensor principle:	magnetic
Number of N/O:	2
Max. current at AC1:	0.0 A
Number of auxiliary contacts:	0
Connection type:	M8, 4pol. male
Switching voltage:	24 V
Type of switching voltage:	DC
Assured switching distance:	8.0 mm
Assured release distance:	26.0 mm
Protection type, housing:	IP65;IP67
Status indicator:	Without LED
Design:	Round
Width dimension:	30.0 mm
Height dimension:	30.0 mm
Depth dimension:	36.0 mm
Gross weight:	47 g
Net weight:	36 g
Ambient temperature:	-10 - 55 °C

Operating modes:

Series connection

Accessories



533110

PSEN Kabel Winkel/cable angleplug 2m



533111

PSEN Kabel Gerade/cable straightplug 2m



533120

PSEN Kabel Winkel/cable angleplug 5m



533121

PSEN Kabel Gerade/cable straightplug 5m



533130

PSEN Kabel Winkel/cable angleplug 10m



533131

PSEN Kabel Gerade/cable straightplug 10m



533140

PSEN Kabel Winkel/cable angleplug 30m



533141

PSEN Kabel Gerade/cable straightplug 30m



535120

PSEN ix1 Interface for 4 PSEN 1

Optional accessories



532110

PSEN Winkel / bracket



533110

PSEN Kabel Winkel/cable angleplug 2m



533111

PSEN Kabel Gerade/cable straightplug 2m



533120

PSEN Kabel Winkel/cable angleplug 5m



533121

PSEN Kabel Gerade/cable straightplug 5m



533130

PSEN Kabel Winkel/cable angleplug 10m



533131

PSEN Kabel Gerade/cable straightplug 10m



533140

PSEN Kabel Winkel/cable angleplug 30m



533141

PSEN Kabel Gerade/cable straightplug 30m



535120

PSEN ix1 Interface for 4 PSEN 1
