


PSEN ma1.4p-57/PSEN ma1.4-03mm/ 1unit

506337



Magnetic safety switch 2 N/O, 1 signal contact N/O, 8-pin M8 connector, square design, LED IP67, operating distance 3 mm, for series connections with PSEN ix1, Height design 18 mm, PU = 1 sensor with actuator.

## Technical details

Housing material:	PBT
Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV
Sensor principle:	magnetic
Number of N/O:	2
Connection type:	M8, 8pol. male
Switching voltage:	24 V
Type of switching voltage:	DC
Assured switching distance:	3.0 mm
Assured release distance:	12.0 mm
Protection type, housing:	IP65;IP67
Status indicator:	With LED
Design:	square
Width dimension:	26.4 mm
Height dimension:	37.0 mm
Depth dimension:	18.0 mm
Gross weight:	77 g
Net weight:	51 g
Ambient temperature:	-10 - 55 °C
Operating modes:	Series connection

## Accessories



533150

PSEN cable M8-8sf, 2m



533151

PSEN cable M8-8sf, 5m



533152

PSEN cable M8-8sf, 10m



533153

PSEN cable M8-8sf, 20m



533154

PSEN cable M8-8sf, 30m



535120

PSEN ix1 Interface for 4 PSEN 1

## Optional accessories



533150

PSEN cable M8-8sf, 2m



533151

PSEN cable M8-8sf, 5m



533152

PSEN cable M8-8sf, 10m

---



533153

PSEN cable M8-8sf, 20m

---



533154

PSEN cable M8-8sf, 30m

---



533155

PSEN cable M8-8sf M8-sm, 0.5m

---



533156

PSEN cable M8-8sf M8-8sm, 1m

---



533157

PSEN cable M8-8sf M8-8sm, 2m

---



535120

PSEN ix1 Interface for 4 PSEN 1

---



540329

PSEN converter M8-8sf -- M12-8sm

---



533162

PSEN cable M8-8af, 10m

---



533159

PSEN cable M8-8sf M8-8sm, 10m

---



533158

PSEN cable M8-8sf M8-8sm, 5m

---



533160

PSEN cable M8-8sf M8-8sm, 20m

---



533161

PSEN cable M8-8sf M8-8sm, 30m

---