

PSEN 2.1-20/1actuator

512120



Magnetic safety switch 2 N/O, square design IP6K9K, height design 13 mm
PU = 1 actuator.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;ECOLAB
Protection type, housing:	IP67;IP69
Design:	square
Width dimension:	26.0 mm
Height dimension:	36.0 mm
Depth dimension:	13.0 mm
Gross weight:	18 g
Net weight:	17 g
Ambient temperature:	-25 - 70 °C

Optional accessories



380200

PSS67 Cable M8sf M12sm, 3m



380201

PSS67 Cable M8sf M12sm, 5m

380202

PSS67 Cable M8sf M12sm, 10m

	380203	PSS67 Cable M8sf M12sm, 30m
	380204	PSS67 Cable M8af M12sm, 3m
	380205	PSS67 Cable M8af M12sm, 5m
	380206	PSS67 Cable M8af M12sm, 10m
	380207	PSS67 Cable M8af M12sm, 30m
	380300	PSEN ma adapter
	532110	PSEN Winkel / bracket
	533110	PSEN Kabel Winkel/cable angleplug 2m
	533111	PSEN Kabel Gerade/cable straightplug 2m

	533120	PSEN Kabel Winkel/cable angleplug 5m
	533121	PSEN Kabel Gerade/cable straightplug 5m
	533130	PSEN Kabel Winkel/cable angleplug 10m
	533131	PSEN Kabel Gerade/cable straightplug 10m
	533140	PSEN Kabel Winkel/cable angleplug 30m
	533141	PSEN Kabel Gerade/cable straightplug 30m
	534310	PSEN Distanzplatte / spacer (10 pcs.)
	534320	PSEN reverse spacer
	773600	PDP67 F 8DI ION



540310

PSEN screw M4x16 10pcs
