

PSEN 1.1b-22/8mm /10m/ix1/1switch

524129



Magnetic safety switch 2 N/O, square design, with 10 m cable (PUR), height design 13 mm IP6K9K, operating distance 8 mm, for applications with PSEN ix1 PU = 1 piece without actuator.

Technical details

Housing material:	PBT
Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;ECOLAB
Sensor principle:	magnetic
Number of N/O:	2
Connection type:	10m Kabel
Switching voltage:	24 V
Type of switching voltage:	DC
Assured switching distance:	8.0 mm
Assured release distance:	26.0 mm
Protection type, housing:	IP67;IP69
Status indicator:	Without LED
Design:	square
Width dimension:	26.0 mm
Height dimension:	36.0 mm
Depth dimension:	13.0 mm
Gross weight:	360 g
Net weight:	340 g
Ambient temperature:	-10 - 70 °C
Operating modes:	Series connection

Accessories



535120

PSEN ix1 Interface for 4 PSEN 1



514120

PSEN 1.1-20 / 1 actuator

Optional accessories



532110

PSEN Winkel / bracket



533110

PSEN Kabel Winkel/cable angleplug 2m



533111

PSEN Kabel Gerade/cable straightplug 2m



533120

PSEN Kabel Winkel/cable angleplug 5m



533121

PSEN Kabel Gerade/cable straightplug 5m



533130

PSEN Kabel Winkel/cable angleplug 10m



533131

PSEN Kabel Gerade/cable straightplug 10m



533140

PSEN Kabel Winkel/cable angleplug 30m



533141

PSEN Kabel Gerade/cable straightplug 30m



534310

PSEN Distanzplatte / spacer (10 pcs.)



534320

PSEN reverse spacer



535120

PSEN ix1 Interface for 4 PSEN 1
