

## PSEN cs3.1p 1switch

541060












RFID safety switch 2 safe semiconductor outputs, 8-pin M8 connector, one direction of actuation IP67; operating distance 11 mm, Sao = 8 mm, Sar = 20 mm; PU = 1 piece coded switch without actuator.

### Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;FCC;IC
Sensor principle:	Transponder
Type of coding:	Coded
Number of OSSD outputs:	2
Number of inputs:	2
Connection type:	M8, 8pol. male
Supply voltage (V):	24,0
Supply voltage type:	DC
Power consumption DC:	1.0 W
Assured switching distance:	8.0 mm
Assured release distance:	20.0 mm
Protection type, housing:	IP6K9K
Width dimension:	26.0 mm
Height dimension:	37.0 mm
Depth dimension:	18.0 mm
Gross weight:	50 g
Net weight:	31 g
Ambient temperature:	-25 - 70 °C

## Accessories

	533150	PSEN cable M8-8sf, 2m
	533151	PSEN cable M8-8sf, 5m
	533152	PSEN cable M8-8sf, 10m
	533153	PSEN cable M8-8sf, 20m
	533154	PSEN cable M8-8sf, 30m
	540080	PSEN cs1.1 1 actuator
	541080	PSEN cs3.1 1 actuator
	541087	PSEN cs3.1 low profile glue 1 actuator
	541088	PSEN cs3.1 low profile screw 1 actuator

## Optional accessories



533150

PSEN cable M8-8sf, 2m



533151

PSEN cable M8-8sf, 5m



533152

PSEN cable M8-8sf, 10m



533153

PSEN cable M8-8sf, 20m



533154

PSEN cable M8-8sf, 30m



533155

PSEN cable M8-8sf M8-sm, 0.5m



533156

PSEN cable M8-8sf M8-8sm, 1m



533157

PSEN cable M8-8sf M8-8sm, 2m



540329

PSEN converter M8-8sf -- M12-8sm



773603

PDP67 F 4 code



540340

PSEN cable M12-8sf M12-8sm, 2m



540341

PSEN cable M12-8sf M12-8sm, 5m



540343

PSEN cable M12-8sf M12-8sm, 20m



540344

PSEN cable M12-8sf M12-8sm, 30m



540342

PSEN cable M12-8sf M12-8sm, 10m



540130

SDD ES ETH



540132

SDD ES PROFIBUS



540337

PSEN Y junction M8-M12/M12 PIGTAIL