

PSEN cs3.1b 1 switch

541062



RFID safety switch 2 safe semiconductor outputs, connection cable 10 m, one direction of actuation IP6K9K, operating distance 11 mm, Sao = 8 mm, Sar = 20 mm; PU = 1 piece coded switch without actuator.

Technical details


| | |
|-----------------------------|---|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;FCC;IC |
| Sensor principle: | Transponder |
| Type of coding: | Coded |
| Number of OSSD outputs: | 2 |
| Number of inputs: | 2 |
| Connection type: | 10m Kabel |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Power consumption DC: | 1.0 W |
| Assured switching distance: | 8.0 mm |
| Assured release distance: | 20.0 mm |
| Protection type, housing: | IP6K9K |
| Width dimension: | 26.0 mm |
| Height dimension: | 37.0 mm |
| Depth dimension: | 18.0 mm |
| Gross weight: | 410 g |
| Net weight: | 380 g |
| Ambient temperature: | -25 - 70 °C |

Accessories



540080

PSEN cs1.1 1 actuator



541080

PSEN cs3.1 1 actuator



541087

PSEN cs3.1 low profile glue 1 actuator



541088

PSEN cs3.1 low profile screw 1 actuator

Optional accessories



540334

PSEN/PDP67 M12-8sm screw terminals



540130

SDD ES ETH



540132

SDD ES PROFIBUS