

PSEN me1M / 1AS

570004



Mechanical safety switch with standard actuator Interlock principle
magnetic force Contacts 2 N/O, 2 N/C Supply voltage 24 V AC/DC.

Technical details

Certifications:	CE;BG;EAC (Eurasian);CCC;cCSAus
Type of guard locking:	Magnetic force
Extraction force:	27 N
Latching force:	1500 N
Auxiliary release:	No
Actuator:	Standard
Number of N/O:	2
Number of N/C:	2
Voltage at AC1:	240 V
Max. current at AC1:	2.5 A
Voltage at AC15:	230 V
Max. current at AC15:	2.5 A
Supply voltage (V):	24,0
Supply voltage type:	AC/DC
Power consumption AC:	4.4 VA
Power consumption DC:	4.4 W
Protection type, housing:	IP67
Width dimension:	42.5 mm
Height dimension:	184.0 mm
Depth dimension:	51.0 mm

Gross weight:	421 g
Net weight:	341 g
Ambient temperature:	-25 - 70 °C

Optional accessories



570101

PSEN me1AS




570102

PSEN me1AR



773600

PDP67 F 8DI ION



540310

PSEN screw M4x16 10pcs



380708

PDP67 cable M12-5sm, 30m



380707

PDP67 cable M12-5sm, 20m



380706

PDP67 cable M12-5sm, 10m



380705

PDP67 cable M12-5sm, 3m