

PSEN me1.2S / 1AR

570007



Mechanical safety switch with radius actuator Interlock principle: Spring force 1500 N; contacts: 2 N/O, 2 N/C Supply voltage 110V - 230 V AC.

Technical details

Certifications:	CE;BG;EAC (Eurasian);CCC;cCSAus
Type of guard locking:	Spring force
Extraction force:	27 N
Latching force:	1500 N
Auxiliary release:	Yes
Actuator:	Radius
Number of N/O:	2
Number of N/C:	2
Voltage at AC1:	240 V
Max. current at AC1:	2.5 A
Voltage at AC15:	230 V
Max. current at AC15:	2.5 A
Supply voltage (V):	110,0
Supply voltage type:	AC
Power consumption AC:	8.0 VA
Protection type, housing:	IP67
Width dimension:	42.5 mm
Height dimension:	184.0 mm
Depth dimension:	51.0 mm
Gross weight:	514 g

Net weight:	335 g
Ambient temperature:	-25 - 70 °C

Optional accessories



570101 PSEN me1AS



570102 PSEN me1AR



773600 PDP67 F 8DI ION



540312 PSEN screw M5x20 10pcs



380708 PDP67 cable M12-5sm, 30m



380707 PDP67 cable M12-5sm, 20m



380706 PDP67 cable M12-5sm, 10m



380705 PDP67 cable M12-5sm, 3m