

PSEN me1.21S / 1AR

570008



Mechanical safety switch with radius actuator Interlock principle: Spring force 1500 N; contacts: 1 N/O, 3 N/C Supply voltage 110V - 230 V AC.

## Technical details

|                           |                                 |
|---------------------------|---------------------------------|
| Certifications:           | CE;BG;EAC (Eurasian);CCC;cCSAus |
| Type of guard locking:    | Spring force                    |
| Extraction force:         | 27 N                            |
| Latching force:           | 1500 N                          |
| Auxiliary release:        | Yes                             |
| Actuator:                 | Radius                          |
| Number of N/O:            | 1                               |
| Number of N/C:            | 3                               |
| Voltage at AC15:          | 230 V                           |
| Max. current at AC15:     | 2.5 A                           |
| Supply voltage (V):       | 110,0                           |
| Supply voltage type:      | AC                              |
| Power consumption AC:     | 8.0 VA                          |
| Protection type, housing: | IP67                            |
| Width dimension:          | 42.5 mm                         |
| Height dimension:         | 184.0 mm                        |
| Depth dimension:          | 51.0 mm                         |
| Gross weight:             | 515 g                           |
| Net weight:               | 337 g                           |
| Ambient temperature:      | -25 - 70 °C                     |

## Optional accessories



570101

PSEN me1AS



570102

PSEN me1AR



773600

PDP67 F 8DI ION



540312

PSEN screw M5x20 10pcs



380708

PDP67 cable M12-5sm, 30m



380707

PDP67 cable M12-5sm, 20m



380706

PDP67 cable M12-5sm, 10m



380705

PDP67 cable M12-5sm, 3m