

PSEN op4H-s-30-060/1

630763











Safety light curtain, type 4, PL e, hand protection (resolution 30 mm)
Protected field height 600 mm, supply voltage 24 V, connector M12,
sender: 4-pin, receiver: 8-pin, Connection cable not supplied with the unit.









Technical details

| | |
|-----------------------------------|------------------------------------|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV |
| Sensor principle: | Optical |
| Type in accordance with EC 61496: | 4 |
| Resolution of safety device: | 30 mm |
| Number of beams: | 24 |
| Resolution, protection type: | Hand |
| Height of protected field: | 600 mm |
| Operating range (m): | 0,2 - 19,0 |
| Reaction time: | 14.00 ms |
| Number of OSSD outputs: | 2 |
| Blanking: | No |
| Muting: | No |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Protection type, housing: | IP65 |
| Application in accordance with: | CLC/TS 61496-2;EN 61496-1 |
| Width dimension: | 32.3 mm |
| Height dimension: | 683.2 mm |
| Depth dimension: | 36.9 mm |
| Gross weight: | 3360 g |

| | |
|----------------------|-----------|
| Net weight: | 2360 g |
| Ambient temperature: | 0 - 55 °C |

Accessories

| | | |
|---|--------|--|
|  | 630303 | PSEN op cable axial M12 4-p. shield. 3m |
|  | 630304 | PSEN op cable axial M12 4-p. shield. 5m |
|  | 630305 | PSEN op cable axial M12 4-p. shield. 10m |
|  | 630306 | PSEN op cable angle M12 4-p. shield. 3m |
|  | 630307 | PSEN op cable angle M12 4-p. shield. 5m |
|  | 630308 | PSEN op cable angle M12 4-p. shield. 10m |
|  | 630309 | PSEN op cable axial M12 4-p. shield. 30m |
|  | 630313 | PSEN op cable axial M12 8-p. shield. 3m |

| | | |
|---|--------|--|
|  | 630314 | PSEN op cable axial M12 8-p. shield. 5m |
|  | 630315 | PSEN op cable axial M12 8-p. shield. 10m |
|  | 630316 | PSEN op cable angle M12 8-p. shield. 3m |
|  | 630317 | PSEN op cable angle M12 8-p. shield. 5m |
|  | 630318 | PSEN op cable angle M12 8-p. shield. 10m |
|  | 630319 | PSEN op cable angle M12 4-p. shield. 30m |
|  | 630328 | PSEN op cable axial M12 8-p. shield. 30m |
|  | 630329 | PSEN op cable angle M12 8-p. shield. 30m |