

PSEN sc L 3.0 08-12

6D000012



Light - Model, 40mm / 70mm detection capability, muting, override, EDM, restart applications according to EN ISO 61496-3, vertical applications, reference points, measurement date output (UDP), exchangeable memory block, fast replacement; 3.0m safety zone; 1 safety zone in parallel active, 1 warning zone in parallel active, 3 zone set switches, 10 configurable zone sets

Technical details

| | |
|--|---------------------|
| Certifications: | CE;cULus Listed;TÜV |
| Operating range warning zone: | 40 m |
| Rotation time: | 30 ms |
| Selectable resolutions: | 70 mm |
| No. of safety zones simultaneous mon.: | 1 |
| No. of zones simultaneous monitoring: | 2 |
| Number of zone configurations: | 10 |
| Width dimension: | 102.0 mm |
| Height dimension: | 152.0 mm |
| Depth dimension: | 112.5 mm |
| Gross weight: | 2140 g |
| Net weight: | 1530 g |
| Ambient temperature: | 0 - 50 °C |

Accessories



540319

PSEN cable axial M12 8-pole 3m



540320

PSEN cable axial M12 8-pole 5m



540321

PSEN cable axial M12 8-pole 10m



540326

PSEN cable axial M12 8-pole 30m



6D000004

PSEN sc bracket H



6D000002

PSEN sc bracket PR



6D000003

PSEN sc bracket P



570355

PSEN cable M12-12sf 30m



570351

PSEN cable M12-12sf 3m



570352

PSEN cable M12-12sf 5m



570350

PSEN cable M12-12sf 2m



570354

PSEN cable M12-12sf 20m



570353

PSEN cable M12-12sf 10m



570356

PSEN cable M12-12sf 50m



6D000010

PSEN sc bracket F



6D000011

PSEN sc bracket C

Optional accessories



6D000006

PSEN sc memory 08-12