

PSEN sc M 3.0 08-12

6D000016



Master - Model, master of series-connection up to 3 slaves, 40mm / 70mm detection capability, muting, override, EDM, restart applications according to EN ISO 61496-3, vertical applications, reference points, measurement date output (UDP), exchangeable memory block, fast replacement; 3.0m safety zone; 1 safety zone in parallel active, 1 warning zone in parallel active, 3 zone set switches, 10 configurable zone sets

Technical details

Certifications:	CE;cULus Listed;TÜV
Operating range warning zone:	40 m
Rotation time:	30 ms
Selectable resolutions:	70 mm
No. of safety zones simultaneous mon.:	1
No. of zones simultaneous monitoring:	2
Number of zone configurations:	10
Width dimension:	102.0 mm
Height dimension:	152.0 mm
Depth dimension:	112.5 mm
Gross weight:	2140 g
Net weight:	1530 g
Ambient temperature:	0 - 50 °C

Accessories



540319

PSEN cable axial M12 8-pole 3m



540320

PSEN cable axial M12 8-pole 5m



540321

PSEN cable axial M12 8-pole 10m



540326

PSEN cable axial M12 8-pole 30m



6D000004

PSEN sc bracket H



6D000002

PSEN sc bracket PR



6D000003

PSEN sc bracket P



570355

PSEN cable M12-12sf 30m



570351

PSEN cable M12-12sf 3m



570352

PSEN cable M12-12sf 5m



570350

PSEN cable M12-12sf 2m



570354

PSEN cable M12-12sf 20m



570353

PSEN cable M12-12sf 10m



570356

PSEN cable M12-12sf 50m



6D000010

PSEN sc bracket F



6D000011

PSEN sc bracket C



6D000026

PSEN sc cable CAT5e M12-8sm/M12-8sm, 20m



6D000025

PSEN sc cable CAT5e M12-8sm/M12-8sm, 10m



6D000022

PSEN sc cable CAT5e M12-8sm/M12-8sm, 1m



6D000024

PSEN sc cable CAT5e M12-8sm/M12-8sm, 5m



6D000023

PSEN sc cable CAT5e M12-8sm/M12-8sm, 3m

Optional accessories



6D000006

PSEN sc memory 08-12