

## PNOZ s1 24VDC 2 n/o

750101



PNOZsigma Safety relay (standalone). Inputs: 1-channel wiring. Outputs: 2 N/O, 1 semiconductor. UB 24 V DC, width: 12.5 mm. Plug-in terminals of screw type Monitoring E-STOP, safety gates.

### Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;KOSHA;CCC
Application options:	Instantaneous E-STOP monitoring;Limit switch;Safety gate monitor
Operating modes:	Single-channel;Automatic reset;Manual reset
Product standard:	EN 60947-5-1
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal style:	Plug-in
Terminal type:	Screw terminal
Number of instantaneous safety contacts:	2
Number of delayed safety contacts:	0
Number of auxiliary contacts:	0
Number of semiconductor outputs:	1
Stop category:	0
Max. current at DC13 I (6 cycles/min):	1.5 A
Max. current at AC15:	1.5 A
Width dimension:	12.5 mm
Height dimension:	98.0 mm
Depth dimension:	120.0 mm
Gross weight:	115 g

Net weight:	105 g
Ambient temperature:	-10 - 55 °C

## Optional accessories



750002

PNOZ s Setscrew terminals 12,5mm



750010

PNOZ s terminator plug ( 10 pieces)