

PNOZ s2 24VDC 3 n/o 1 n/c

750102



PNOZsigma Safety relay (standalone). Inputs: Single-channel wiring
Outputs: 3 N/O, 1 N/C, 1 semiconductor. UB 24 V DC, width: 17.5 mm.
Plug-in terminals of screw type Monitoring E-STOP, safety gates.

Technical details

| | |
|--|--|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;KOSHA;CCC |
| Application options: | Instantaneous E-STOP monitoring;Limit switch;Safety gate monitor |
| Operating modes: | Single-channel;Automatic reset;Manual reset;Monitored manual reset |
| Product standard: | EN 60947-5-1 |
| Standards: | EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1 |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Terminal style: | Plug-in |
| Terminal type: | Screw terminal |
| Number of instantaneous safety contacts: | 3 |
| Number of delayed safety contacts: | 0 |
| Number of auxiliary contacts: | 1 |
| Number of semiconductor outputs: | 1 |
| Stop category: | 0 |
| Max. current at DC13 I (6 cycles/min): | 5.0 A |
| Max. current at AC15: | 5.0 A |
| Width dimension: | 17.5 mm |
| Height dimension: | 98.0 mm |
| Depth dimension: | 120.0 mm |
| Gross weight: | 185 g |

| | |
|----------------------|-------------|
| Net weight: | 175 g |
| Ambient temperature: | -10 - 55 °C |

Optional accessories



750003

PNOZ s Setscrew terminals 17,5mm



750010

PNOZ s terminator plug (10 pieces)