

PNOZ s10 24VDC 4 n/o 1 n/c

750110



PNOZsigma Contact expansion. Outputs: 4 N/O, 1 N/C. UB 24V DC, switching load: 12 A DC1, Width: 45 mm, plug-in terminals of screw type. Contact block for contact expansion in connection with safety-related control components.

Technical details

| | |
|------------------------------------------|------------------------------------------------------------|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;KOSHA;CCC |
| Application options: | Instantaneous contact expansion |
| Supply voltage (V): | 24,0 |
| Max. current at DC1: | 12.0 A |
| Voltage at AC1: | 240 V |
| Terminal type: | Screw terminal |
| Terminal style: | Plug-in |
| Standards: | EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1 |
| Operating modes: | Single-channel;without detection of shorts across contacts |
| Number of instantaneous safety contacts: | 4 |
| Number of instantaneous safety outputs: | 0 ST |
| Width dimension: | 45.0 mm |
| Height dimension: | 98.0 mm |
| Depth dimension: | 120.0 mm |
| Gross weight: | 310 g |
| Net weight: | 295 g |
| Ambient temperature: | -10 - 55 °C |

Optional accessories



750008

PNOZ s Set1 screw terminals 45mm



750020

PNOZ s connector (10 pieces)