

PNOZ s1 C 24VDC 2 n/o

751101



PNOZsigma Safety relay (standalone). Inputs: Single-channel wiring. Outputs: 2 N/O, 1 semiconductor UB 24 V DC, width: 12.5 mm, plug-in spring-loaded terminals Monitoring E-STOP, safety gates.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;KOSHA;CCC
Application options:	Instantaneous E-STOP monitoring;Limit switch;Safety gate monitor
Operating modes:	Single-channel;Automatic reset;Manual reset
Product standard:	EN 60947-5-1
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal style:	Plug-in
Terminal type:	Spring-loaded terminal
Number of instantaneous safety contacts:	2
Number of delayed safety contacts:	0
Number of auxiliary contacts:	0
Number of semiconductor outputs:	1
Stop category:	0
Max. current at DC13 I (6 cycles/min):	1.5 A
Max. current at AC15:	1.5 A
Width dimension:	12.5 mm
Height dimension:	100.0 mm
Depth dimension:	120.0 mm
Gross weight:	115 g

Net weight:	105 g
Ambient temperature:	-10 - 55 °C

Optional accessories



751002

PNOZ s Setspring loaded terminals 12,5mm



750010

PNOZ s terminator plug (10 pieces)