

PNOZ s6 C 48-240VACDC 3 n/o 1 n/c

751136



PNOZsigma Safety relay (standalone). Inputs: 1 N/O, 1 N/C per pushbutton. Outputs: 3 N/O, 1 N/C, 1 semiconductor UB 48 - 240V AC/DC, width: 22.5 mm, plug-in spring-loaded terminals. Two-hand control device, monitoring the simultaneity of a two-hand pushbutton.

Technical details

| | |
|----------------------|--|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;KOSHA;CCC |
| Application options: | Two-hand monitoring Type III C |
| Max. current at DC1: | 6.0 A |
| Voltage at AC1: | 240 V |
| Terminal type: | Spring-loaded terminal |
| Terminal style: | Plug-in |
| Stop category: | 0 |
| Standards: | EN 574 TYP III C;EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1 |
| Operating modes: | Dual-channel;Detection of shorts across contacts |
| Supply voltage (V): | 48,0 - 240,0 |
| Width dimension: | 22.5 mm |
| Height dimension: | 100.0 mm |
| Depth dimension: | 120.0 mm |
| Gross weight: | 215 g |
| Net weight: | 205 g |
| Ambient temperature: | -10 - 55 °C |

Optional accessories



751004

PNOZ s Setspring loaded terminals 22,5mm



750010

PNOZ s terminator plug (10 pieces)