

PMD s20 24-240VAC/DC 10-200k / 2U

760120



Insulation monitor in the Sigma housing for monitoring the insulation of galvanically isolated supplies. Limit values can be set via display, can be saved on chip card. Relay output: 2 switch contacts. Analogue output: Current 4 - 20 mA and 0 - 10 V DC, supply voltage: 24 - 240 V AC/DC, screw terminals.

Technical details

Certifications:	CE;cULus Listed
Application options:	Insulation monitor;Earth fault monitor
Supply voltage (V):	24,0 - 240,0
Supply voltage type:	AC/DC
Insulation resistance:	10 ... 200 kOhm
Max. cable length unshielded:	0 ... 400 V
Protection type, housing:	IP40
Terminal type:	Screw terminal
Terminal style:	Plug-in
Operating modes:	Normally de-energised mode;Fault non-latching;Fault latching;Normally energised mode;Automatic reset;Manual reset;Test mode;Normal operation
Width dimension:	45.0 mm
Height dimension:	98.0 mm
Depth dimension:	120.0 mm
Gross weight:	295 g
Net weight:	264 g
Ambient temperature:	-10 - 55 °C

Accessories



750008

PNOZ s Set1screw terminals 45mm

Optional accessories



750012

PNOZ s Set2screw terminals 45mm



779211

Chipcard 1 piece 32kB