

PNOZ m B1

772101




Configurable control system PNOZmulti 2 base module expandable, communication interface, 2 Ethernet interfaces, USB memory.

Technical details

| | |
|--|--|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;KOSHA |
| Number of test pulse outputs: | 4 |
| Power consumption DC: | 18.5 W |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Base unit: | Yes |
| Terminal type: | Cage clamp terminal;Screw terminal |
| Terminal style: | Plug-in |
| Version for extreme environ. conditions: | Standard |
| Width dimension: | 45.0 mm |
| Height dimension: | 101.4 mm |
| Depth dimension: | 120.2 mm |
| Gross weight: | 219 g |
| Net weight: | 209 g |
| Ambient temperature: | 0 - 60 °C |

Accessories



773010B

Basic Licence for PNOZmulti Config.



751016

Set4 Spring Terminals



750016

Set4 Screw Terminals

Optional accessories



380401

RJ45 Connector



773010K

User Licence for PNOZmulti Config



773010U

Basic Upgr Licence for PNOZmulti Config



773011B

Basic Licence for PNOZmulti Service




773011K

User Licence for PNOZmulti Service



773011U

Basic Upgr Licence for PNOZmulti Service



773011V

User Upgr Licence for PNOZmulti Service



779213

USB Memory 512MB

Alternatives



772100

PNOZ m B0

Related Products



773616

PDP67 F 8DI ION PT



773615

PDP67 F 8DI ION HP VA



773614

PDP67 F 8DI ION VA



773601

PDP67 F 8DI ION HP



773600

PDP67 F 8DI ION



772181

PNOZ m ES 14DO



772171

PNOZ m EF 2MM



772170

PNOZ m EF 1MM



772160

PNOZ m EF 4AI



772144

PNOZ m EF 8DI2DOT



772143

PNOZ m EF 4DI4DOR



772142

PNOZ m EF 8DI4DO



772140

PNOZ m EF 16DI



772138

PNOZ m ES Profinet



772137

PNOZ m ES EtherNet/IP



772136

PNOZ m ES EtherCAT



772135

PNOZ m ES CC-Link



772134

PNOZ m ES CANopen



772132

PNOZ m ES Profibus



772122

PNOZ m EF SafetyNET



772121

PNOZ m EF PDP Link



772120

PNOZ m EF Multi Link



772119

PNOZ m ES Powerlink
