

PNOZ m EF PDP Link

772121



Configurable control system PNOZmulti 2 expansion module Connection decentralised I/O module.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;KOSHA
Power consumption DC:	100.0 W
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal type:	Screw terminal;Spring-loaded terminal
Terminal style:	Plug-in
Version for extreme environ. conditions:	Standard
Width dimension:	22.5 mm
Height dimension:	101.4 mm
Depth dimension:	120.0 mm
Gross weight:	117 g
Net weight:	96 g
Ambient temperature:	0 - 60 °C

Accessories



783540

Spring terminals PNOZ mml2p



793540

Screw terminals PNOZ mml2p

Optional accessories

311074 PSS SB BUSCABLE LC



380320 PSS67 I/O Cable



779260 PNOZ mm0.xp connector left (10 pcs)



783541 Spring terminals PNOZ mml2p 10 pcs.



793541 Screw terminals PNOZ mml2p 10 pcs.

Related Products



773616 PDP67 F 8DI ION PT



773615 PDP67 F 8DI ION HP VA



773614 PDP67 F 8DI ION VA



773601

PDP67 F 8DI ION HP



773600

PDP67 F 8DI ION



772171

PNOZ m EF 2MM



772170

PNOZ m EF 1MM



772160

PNOZ m EF 4AI



772144

PNOZ m EF 8DI2DOT



772143

PNOZ m EF 4DI4DOR



772142

PNOZ m EF 8DI4DO



772140

PNOZ m EF 16DI



772138

PNOZ m ES Profinet



772137

PNOZ m ES EtherNet/IP



772136

PNOZ m ES EtherCAT



772135

PNOZ m ES CC-Link



772134

PNOZ m ES CANopen



772132

PNOZ m ES Profibus



772131

PNOZ m ES RS232



772130

PNOZ m ES ETH



772122

PNOZ m EF SafetyNET



772120

PNOZ m EF Multi Link



772119

PNOZ m ES Powerlink



772101

PNOZ m B1



772100

PNOZ m B0
