

## PNOZ m EF SafetyNET

772122



Safe communication module SafetyNET p for PNOZ m Bxp

### Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV
Fieldbus interface:	SafetyNET p
Version for extreme environ. conditions:	Standard
Width dimension:	45.0 mm
Height dimension:	101.4 mm
Depth dimension:	110.4 mm
Gross weight:	190 g
Net weight:	180 g
Ambient temperature:	0 - 60 °C

### Accessories



380401

RJ45 Connector



380000

SafetyNET p Cable per mtr



750017

Set 5 Screw Terminals



751017

Set 5 Spring Terminals

## Optional accessories



779260

PNOZ mm0.xp connector left (10 pcs)

## Alternatives



772120

PNOZ m EF Multi Link

## Related Products



773616

PDP67 F 8DI ION PT



773615

PDP67 F 8DI ION HP VA



773614

PDP67 F 8DI ION VA



773601

PDP67 F 8DI ION HP



773600

PDP67 F 8DI ION



772171

PNOZ m EF 2MM

---



772170

PNOZ m EF 1MM

---



772160

PNOZ m EF 4AI

---



772144

PNOZ m EF 8DI2DOT

---



772143

PNOZ m EF 4DI4DOR

---



772142

PNOZ m EF 8DI4DO

---



772140

PNOZ m EF 16DI

---



772138

PNOZ m ES Profinet

---



772137

PNOZ m ES EtherNet/IP

---



772136

PNOZ m ES EtherCAT

---



772135

PNOZ m ES CC-Link

---



772134

PNOZ m ES CANopen

---



772132

PNOZ m ES Profibus

---



772131

PNOZ m ES RS232

---



772130

PNOZ m ES ETH

---



772121

PNOZ m EF PDP Link

---



772120

PNOZ m EF Multi Link

---



772119

PNOZ m ES Powerlink

---



772101

PNOZ m B1



772100

PNOZ m B0