

## PNOZ m EF 8DI4DO

772142



Configurable control system PNOZmulti 2 expansion module 8 safe digital inputs, 4 safe semiconductor outputs.

### Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;KOSHA
Number of digital inputs:	8
Positive switching 1-pole SC output:	4
Supply voltage 2 (V):	24
Supply voltage type 2:	DC
Terminal type:	Screw terminal;Spring-loaded terminal
Terminal style:	Plug-in
Version for extreme environ. conditions:	Standard
Width dimension:	22.5 mm
Height dimension:	101.4 mm
Depth dimension:	120.0 mm
Gross weight:	115 g
Net weight:	105 g
Ambient temperature:	0 - 60 °C

### Accessories



750004

PNOZ s Setscrew terminals 22,5mm



751004

PNOZ s Setspring loaded terminals 22,5mm

## Optional accessories



779260

PNOZ mm0.xp connector left (10 pcs)

## Alternatives



772140

PNOZ m EF 16DI



772143

PNOZ m EF 4DI4DOR



772144

PNOZ m EF 8DI2DOT

## Related Products



773616

PDP67 F 8DI ION PT



773615

PDP67 F 8DI ION HP VA



773614

PDP67 F 8DI ION VA



773601

PDP67 F 8DI ION HP



773600

PDP67 F 8DI ION



772171

PNOZ m EF 2MM



772170

PNOZ m EF 1MM



772160

PNOZ m EF 4AI



772144

PNOZ m EF 8DI2DOT



772143

PNOZ m EF 4DI4DOR



772140

PNOZ m EF 16DI



772138

PNOZ m ES Profinet



772137

PNOZ m ES EtherNet/IP

---



772136

PNOZ m ES EtherCAT

---



772135

PNOZ m ES CC-Link

---



772134

PNOZ m ES CANopen

---



772132

PNOZ m ES Profibus

---



772131

PNOZ m ES RS232

---



772130

PNOZ m ES ETH

---



772122

PNOZ m EF SafetyNET

---



772121

PNOZ m EF PDP Link

---



772120

PNOZ m EF Multi Link

---



772119

PNOZ m ES Powerlink

---



772101

PNOZ m B1

---



772100

PNOZ m B0

---