

PNOZ p1p 24VDC 2so

773300



Safety relay (standalone) Input: 1-/2-channel wiring with/without detection of shorts across contacts Outputs: 2 semiconductor outputs, Automatic/monitored start. UB 24 V DC, plug-in terminals of screw type. Base module Safety relays PNOZpower.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV
Application options:	Instantaneous E-STOP monitoring;Safety gate monitor
Operating modes:	Single-channel;Automatic reset;Dual-channel;Manual reset;Detection of shorts across contacts;Monitored manual reset;without detection of shorts across contacts
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal style:	Plug-in
Terminal type:	Screw terminal
Number of semiconductor outputs:	2
Width dimension:	45.0 mm
Height dimension:	94.0 mm
Depth dimension:	135.0 mm
Gross weight:	295 g
Net weight:	285 g
Ambient temperature:	-10 - 55 °C

Accessories



773630

PNOZ po3.1p 8n/o



773631

PNOZ po3.2p 4n/o



773632

PNOZ po3.3p 3n/o



773634

PNOZ po3p 3n/o 1n/c



773635

PNOZ po4p 4n/o



773950

PNOZ p1vp 30s



773951

PNOZ p1vp 300s

Optional accessories




773200

PNOZ pps1p 100-240VAC



773900

PNOZ pe1p



779125

PNOZpe2p Bus-Interface
