

PZW 30/24VDC 1n/o 2n/c

774019



Safety relay (standalone) Inputs: Single-channel wiring Outputs: 1 N/O, 2 N/C UB 24 V DC, width: 45 mm, integral screw terminals Pulse timer, pulse times 12 stages from 0 - 30 s.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV
Application options:	Safe pulsing timer
Operating modes:	Single-channel
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal style:	fixed
Terminal type:	Screw terminal
Number of delayed safety contacts:	1
Safety contact delay type:	pulsing
Number of delayed auxiliary contacts:	2
Auxiliary contact delay type:	pulsing
Selectable times:	0,50 s;1,00 s;10,00 s;15,00 s;2,00 s;20,00 s;25,00 s;3,00 s;30,00 s;4,00 s;5,00 s;7,00 s
Stop category:	0
Max. current at DC13 I (6 cycles/min):	3.0 A
Max. current at AC15:	4.0 A
Width dimension:	45.0 mm
Height dimension:	87.0 mm
Depth dimension:	121.0 mm
Gross weight:	265 g

Net weight:

255 g

Ambient temperature:

-10 - 55 °C

Optional accessories



774090

COVER P-93