

PZA 30/110-120VAC 1n/o 2n/c

774035



Safety relay (standalone) Inputs: Single-channel wiring Outputs: 1 N/O, 2 N/C UB 110-120 V AC, width: 45 mm, integral screw terminals, delay-on energisation pulse timer, pulse times 12 stages from 0 - 30 s.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;CCC
Application options:	Safe delay-on energisation timer
Operating modes:	Single-channel
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	110,0 - 120,0
Supply voltage type:	AC
Terminal style:	fixed
Terminal type:	Screw terminal
Number of delayed safety contacts:	1
Safety contact delay type:	delay-on energisation
Number of delayed auxiliary contacts:	2
Auxiliary contact delay type:	delay-on energisation
Selectable times:	12,00 s;15,00 s;18,00 s;21,00 s;24,00 s;27,00 s;3,00 s;30,00 s;4,00 s;5,00 s;7,00 s;9,00 s
Stop category:	0
Max. current at DC13 I (6 cycles/min):	3.0 A
Max. current at AC15:	4.0 A
Width dimension:	45.0 mm
Height dimension:	87.0 mm
Depth dimension:	121.0 mm
Gross weight:	360 g

Net weight:	350 g
Ambient temperature:	-10 - 55 °C

Optional accessories



774090

COVER P-93