

PZA 3/24VDC 1n/o 2n/c

774041



Safety relay (standalone) Inputs: Single-channel wiring Outputs: 1 N/O, 2 N/C UB 24 V DC, width: 45 mm, integral screw terminals, delay-on energisation pulse timer, pulse times 12 stages from 0 - 3 s.

Technical details

| | |
|--|---|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;CCC |
| Application options: | Safe delay-on energisation timer |
| Operating modes: | Single-channel |
| Standards: | EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1 |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Terminal style: | fixed |
| Terminal type: | Screw terminal |
| Number of delayed safety contacts: | 1 |
| Safety contact delay type: | delay-on energisation |
| Number of delayed auxiliary contacts: | 2 |
| Auxiliary contact delay type: | delay-on energisation |
| Selectable times: | 0,30 s;0,40 s;0,50 s;0,70 s;0,90 s;1,20 s;1,50 s;1,80 s;2,10 s;2,40 s;2,70 s;3,00 s |
| Stop category: | 0 |
| Max. current at DC13 I (6 cycles/min): | 3.0 A |
| Max. current at AC15: | 4.0 A |
| Width dimension: | 45.0 mm |
| Height dimension: | 87.0 mm |
| Depth dimension: | 121.0 mm |
| Gross weight: | 265 g |

Net weight:

255 g

Ambient temperature:

-10 - 55 °C

Optional accessories



774090

COVER P-93