

PNOZ 15 24VDC 3n/o 1n/c 1n/c

774050



Safety relay (standalone) Inputs: Single-channel wiring Outputs: 3 N/O, 1 N/C, 1 N/O, 1 semiconductor. Automatic/manual reset UB 24 V DC, width: 90 mm, integral screw terminals, Monitoring E-STOP, safety gates.

Technical details

Certifications:	CE;TÜV;CCC
Application options:	Instantaneous E-STOP monitoring;Safety gate monitor
Operating modes:	Single-channel;Automatic reset;Dual-channel;Manual reset;Detection of shorts across contacts;without detection of shorts across contacts
Product standard:	EN 60947-5-1
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal style:	fixed
Terminal type:	Screw terminal
Number of instantaneous safety contacts:	3
Number of delayed safety contacts:	0
Number of auxiliary contacts:	1
Number of semiconductor outputs:	1
Stop category:	0
Max. current at DC13 I (6 cycles/min):	7.0 A
Max. current at AC15:	5.0 A
Width dimension:	90.0 mm
Height dimension:	87.0 mm
Depth dimension:	121.0 mm

Gross weight:	475 g
Net weight:	465 g
Ambient temperature:	-10 - 55 °C