

## PNOZ 16 24VAC 24VDC 2n/o

774060



Safety relay (standalone) Inputs: 1- / 2-channel wiring with detection of shorts across contacts Outputs: 2 N/O UB 24 V AC/DC, width: 45 mm, integral screw terminals, Monitoring E-STOP, safety gates, pressure sensitive mats (in accordance with the short circuit principle).

### Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;CCC
Application options:	Instantaneous E-STOP monitoring;Limit switch;Pressure sensitive edge;Pressure sensitive mat;Safety gate monitor
Operating modes:	Single-channel;Automatic reset;Dual-channel;Manual reset;Detection of shorts across contacts
Product standard:	EN 60947-5-1
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Number of instantaneous safety contacts:	2
Supply voltage (V):	24,0
Supply voltage type:	AC
Supply voltage 2 (V):	24
Supply voltage type 2:	DC
Terminal style:	fixed
Terminal type:	Screw terminal
Stop category:	0
Max. current at DC13 I (6 cycles/min):	6.0 A
Max. current at AC15:	5.0 A
Width dimension:	45.0 mm
Height dimension:	87.0 mm
Depth dimension:	121.0 mm
Gross weight:	345 g

Net weight:

335 g

Ambient temperature:

-10 - 55 °C

## Optional accessories



774090

COVER P-93