

PNOZ e2.1p 24VDC 2so

774136



Safety relay (standalone) Inputs: Requirement class IIIC in accordance with EN 574 Outputs: 2 safety outputs, 1 auxiliary output in semiconductor technology UB 24 V DC, width: 22.5 mm, plug-in terminals of screw type. Automatic start, connecting several devices.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV
Application options:	Two-hand monitoring Type III C
Operating modes:	Automatic reset;Dual-channel;Detection of shorts across contacts;Self test;with AND input;With OR input
Product standard:	EN 60947-5-1
Standards:	EN 574 TYP III C;EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal type:	Screw terminal
Terminal style:	Plug-in
Number of instantaneous safety outputs:	2 ST
Number of test pulse outputs:	2
Stop category:	0
Width dimension:	22.5 mm
Height dimension:	94.0 mm
Depth dimension:	121.0 mm
Gross weight:	145 g
Net weight:	130 g
Ambient temperature:	-10 - 55 °C

Optional accessories



374280

PNOZ X Set plug in screw terminals P1+P2



774195

Terminal block filter 1



774196

Terminal block filter 2