

PNOZ e5.13p 24VDC 2so

774191



Safety relay (standalone) Inputs: 1-/2-channel wiring without detection of shorts across contacts Outputs: 2 safety outputs + 1 auxiliary output in semiconductor technology, delayed internal AND operation, automatic/monitored start, UB 24 V DC, Width: 22.5 mm, plug-in terminals of screw type, connecting several devices, E-STOP & safety gate monitor, evaluation device safety sensor.

Technical details

| | |
|---|--|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV |
| Application options: | Instantaneous E-STOP monitoring;Limit switch;Light beam device mon. Type 2 with t/p;Light beam device mon. Type 2 w/o t/p;Safety gate monitor |
| Operating modes: | Single-channel;Automatic reset;Dual-channel;Detection of shorts across contacts;Start-up testing;Monitored manual reset;without detection of shorts across contacts;Self test;with AND input;With OR input |
| Product standard: | EN 60947-5-1 |
| Standards: | DIN V VDE 801-1/A1;EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1;VDE 0116 |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Terminal type: | Screw terminal |
| Terminal style: | Plug-in |
| Number of instantaneous safety outputs: | 2 ST |
| Number of test pulse outputs: | 1 |
| Stop category: | 0 |
| Width dimension: | 22.5 mm |
| Height dimension: | 94.0 mm |
| Depth dimension: | 121.0 mm |
| Gross weight: | 145 g |
| Net weight: | 130 g |

Ambient temperature:

-10 - 55 °C

Optional accessories



374280

PNOZ X Set plug in screw terminals P1+P2



774195

Terminal block filter 1



774196

Terminal block filter 2