

P2HZ X3 24VDC 2n/o 1n/c

774350



Safety relay (standalone) Inputs: 1 N/O, 1 N/C per pushbutton Outputs: 2 N/O, 1 N/C UB 24 V DC, width: 22.5 mm, integral screw terminals, two-hand control device, monitoring the simultaneity of a two-hand pushbutton.

Technical details

| | |
|--|---|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;CCC |
| Application options: | Two-hand monitoring Type III C |
| Standards: | EN 574 TYP III C;EN 62061;EN ISO 13849-1;VDE 0113-1 |
| Operating modes: | Dual-channel;Detection of shorts across contacts |
| Number of instantaneous safety contacts: | 2 |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Terminal style: | fixed |
| Terminal type: | Screw terminal |
| Stop category: | 0 |
| Max. current at DC13 I (6 cycles/min): | 1.5 A |
| Width dimension: | 22.5 mm |
| Height dimension: | 87.0 mm |
| Depth dimension: | 121.0 mm |
| Gross weight: | 220 g |
| Net weight: | 210 g |
| Ambient temperature: | -25 - 55 °C |