

PNOZ X2.4V 1/24VDC 4n/o 1so fix

774517



Safety relay (standalone) Inputs: 1-/2-channel wiring with/without detection of shorts across contacts Outputs: 4 N/O delayed, 1 semiconductor instantaneous UB 24 V DC, width: 45 mm, integral screw terminals, Monitoring E-STOP, safety gates with 4 delay-on de-energisation contacts. Release time 1 s fixed and retriggerable.

Technical details

Certifications:	CE;EAC (Eurasian);TÜV;CCC
Application options:	Instantaneous E-STOP monitoring;Limit switch;Safety gate monitor;Delayed E-STOP monitoring
Operating modes:	Single-channel;Automatic reset;Dual-channel;Manual reset;Detection of shorts across contacts
Product standard:	EN 60947-5-1
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal style:	fixed
Terminal type:	Screw terminal
Number of instantaneous safety contacts:	0
Number of delayed safety contacts:	4
Safety contact delay type:	Delay-on de-energisation
Number of semiconductor outputs:	1
Selectable times:	1,00 s
Stop category:	0/1
Max. current at DC13 I (6 cycles/min):	5.0 A
Max. current at AC15:	5.0 A
Width dimension:	45.0 mm
Height dimension:	87.0 mm

Depth dimension:	121.0 mm
Gross weight:	300 g
Net weight:	290 g
Ambient temperature:	-10 - 55 °C