

PNOZ X4 240VAC 3n/o 1n/c

774739



Safety relay (standalone) Inputs: 1-/2-channel wiring with/without detection of shorts across contacts Outputs: 3 N/O, 1 N/C. Automatic/monitored start UB 240 V AC, width: 45 mm, integral screw terminals, Monitoring E-STOP, safety gates.

Technical details

| | |
|--|---|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;CCC |
| Application options: | Instantaneous E-STOP monitoring;Light beam device mon. Type 2 with t/p;Light beam device mon. Type 2 w/o t/p;Light beam device mon. Type 4;Safety gate monitor |
| Operating modes: | Single-channel;Automatic reset;Dual-channel;Manual reset;Detection of shorts across contacts;Monitored manual reset;without detection of shorts across contacts |
| Product standard: | EN 60947-5-1 |
| Standards: | EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1 |
| Supply voltage (V): | 240,0 |
| Supply voltage type: | AC |
| Terminal style: | fixed |
| Terminal type: | Screw terminal |
| Number of instantaneous safety contacts: | 3 |
| Number of delayed safety contacts: | 0 |
| Number of auxiliary contacts: | 1 |
| Number of semiconductor outputs: | 0 |
| Stop category: | 0 |
| Max. current at DC13 I (6 cycles/min): | 7.0 A |
| Max. current at AC15: | 5.0 A |
| Width dimension: | 45.0 mm |
| Height dimension: | 87.0 mm |

| | |
|----------------------|-------------|
| Depth dimension: | 121.0 mm |
| Gross weight: | 380 g |
| Net weight: | 370 g |
| Ambient temperature: | -10 - 55 °C |

Optional accessories



774090

COVER P-93