


## P2HZ X1.10P 24VDC 3n/o 1n/c 2so

777341



Safety relay (standalone) Inputs: 1 N/O, 1 N/C per pushbutton Outputs: 3 N/O, 1 N/C, 2 semiconductor. UB 42 V AC, width: 45 mm plug-in terminals of screw type. Two-hand control device/monitoring the simultaneity of two-hand pushbuttons Sidewards compatibility with P2HZ X1.

## Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;CCC
Application options:	Two-hand monitoring Type III C
Standards:	EN 574 TYP III C;EN 62061;EN ISO 13849-1;VDE 0113-1
Operating modes:	Dual-channel;Detection of shorts across contacts
Number of instantaneous safety contacts:	3
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal style:	Plug-in
Terminal type:	Screw terminal
Stop category:	0
Max. current at DC13 I (6 cycles/min):	1.5 A
Width dimension:	45.0 mm
Height dimension:	94.0 mm
Depth dimension:	121.0 mm
Gross weight:	300 g
Net weight:	290 g
Ambient temperature:	-25 - 55 °C

## Optional accessories



374280

PNOZ X Set plug in screw terminals P1+P2

---