

PZE X4.1P 24VDC 4n/o

777587



Contact expansion Inputs: 1-/2-channel wiring without detection of shorts across contacts Outputs: 4 N/O. UB 24 V DC, width: 22.5 mm plug-in terminals of screw type. Contact block for contact expansion in connection with safety-related control components.

Technical details

| | |
|--|--|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;CCC |
| Application options: | Light beam device mon. Type 2 with t/p;Light beam device mon. Type 2 w/o t/p;Light beam device mon. Type 4;Instantaneous contact expansion |
| Operating modes: | Single-channel;Dual-channel;without detection of shorts across contacts |
| Standards: | EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1 |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Terminal style: | Plug-in |
| Terminal type: | Screw terminal |
| Number of instantaneous safety contacts: | 4 |
| Number of delayed safety contacts: | 0 |
| Max. current at DC13 I (6 cycles/min): | 4.0 A |
| Voltage at AC15: | 230 V |
| Width dimension: | 22.5 mm |
| Height dimension: | 94.0 mm |
| Depth dimension: | 121.0 mm |
| Gross weight: | 195 g |
| Net weight: | 185 g |
| Ambient temperature: | -10 - 55 °C |

Optional accessories



374280

PNOZ X Set plug in screw terminals P1+P2
