

PZE X4.1P 24-240VAC/DC 4n/o

777588



Contact expansion Inputs: 1-/2-channel wiring without detection of shorts across contacts Outputs: 4 N/O. UB 24-240 V AC/DC, width: 45 mm, plug-in terminals of screw type. Contact block for contact expansion in connection with safety-related control components.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;CCC
Application options:	Instantaneous contact expansion
Operating modes:	Single-channel;Dual-channel;without detection of shorts across contacts
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	24,0 - 240,0
Supply voltage type:	AC/DC
Terminal style:	Plug-in
Terminal type:	Screw terminal
Number of instantaneous safety contacts:	4
Number of delayed safety contacts:	0
Max. current at DC13 I (6 cycles/min):	4.0 A
Voltage at AC15:	230 V
Width dimension:	22.5 mm
Height dimension:	94.0 mm
Depth dimension:	121.0 mm
Gross weight:	225 g
Net weight:	215 g
Ambient temperature:	-10 - 55 °C

Optional accessories



374280

PNOZ X Set plug in screw terminals P1+P2
